

OPERATOR INSTRUCTIONS

PREOPERATING INSTRUCTIONS

Remove all packing material and carefully inspect the unit for shipping damage. If any damage is found, file a claim with the delivering carrier immediately.

OPERATING INSTRUCTIONS


Crown PTH50 Series pallet trucks feature a simple raise/neutral/lower method.

- To raise the forks, push the actuating lever down to the RAISE position and pump the handle up and down until full height is reached. The Hydraulic Unit's "top-of-stroke" hydraulic fluid bypass minimizes stress on system when load is raised to maximum lift height. Therefore, excessive pumping will not damage the truck.
- Before maneuvering the truck, move the actuating lever to the NEUTRAL position thereby releasing the handle from additional pumping effort.
- To lower the forks, pull the actuating lever to the LOWER position.



Safe hand pallet truck operation pays off in these three ways:

- You avoid injury and loss of time to yourself.
- You prevent accidents involving fellow employees.
- You prevent damage to the equipment as well as the material you're handling.



ACTUATING



To prevent serious risk of injury to yourself and others, observe the following safety instructions.

- 1. Do not operate this truck unless you are trained and authorized.
- 2. Read and obey all warnings and instructions in the operator's section of this Manual* and on the truck.
- 3. Make sure the truck is in good working order.
- 4. Don't use your pallet truck as a scooter or permit riders.
- 5. Keep your arms, hands, legs and feet away from the load, lift linkage and forks. You or anyone else should never pass or place any body part under the elevated portion of truck or load it is carrying.
- 6. Use neutral position when maneuvering loads. (This reduces operator fatigue).
- 7. Maintain a safe distance from edges of ramps, dockboards and dock.
- 8. A dockboard can move or drop while you are on it. Or you could drive off a dock. Falls from docks or dockboards can cause serious injury or even death. Make sure you are safe.
- 9. Handle only stable loads.
- 10. Don't overload your truck (know its capacity) or yourself. in the long run, you may save time and avoid injury by making more than one trip.
- 11. Position the forks evenly under the load to permit safer movement and easier positioning.
- 12. Don't pick up a load with one fork.
- 13. Avoid moving loads up or down grades, ramps or inclines. Should you have to make an emergency stop, the truck can be stopped by rapidly lowering the load.
- 14. When moving loads up or down grades, ramps or inclines, always work from the high side of the grade. Don't turn. Always travel straight up or down.
- 15. Make sure that ramps, elevators and dockboards have sufficient capacity to handle your load and you.
- 16. Pull, rather than push loads on long distance moves. (It's easier to see where you're going and it's easier to steer your truck!)
- 17. Watch for overhead obstructions when handling tall loads.
- 18. Park your pallet truck in a safe, level place with the handle up and the forks lowered.

Additional copies of this Manual and Truck Labels can be obtained from Crown Equip. Corp., New Bremen, Ohio 45869 U.S.A.

Crown 1994 PF-10140 Printed in U.S.A.